

Datasheet

[Get a Quote](#)

Overview


48*10/100/1000BASE-T ports, 4*GE SFP ports, PoE+, AC power

Quick Specification

Model	S1730S-S48P4S-A1
Part Number	98011347
Memory	512 MB
Flash memory	512 MB
Weight without packaging [kg(lb)]	3.23 kg (7.12 lb)
Weight with packaging [kg(lb)]	4.28 kg (9.44 lb)
Dimensions without packaging (H x W x D) [mm(in.)]	<p>Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 220.0 mm (1.72 in. x 17.4 in. x 8.7 in.)</p> <p>Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 227.0 mm (1.72 in. x 17.4 in. x 8.94 in.)</p>
Dimensions with packaging (H x W x D) [mm(in.)]	90.0 mm x 550.0 mm x 360.0 mm (3.54 in. x 21.65 in. x 14.17 in.)

Product Details:

The Front Panel:



①	48 x 10/100/1000Base-T (PoE+) ports
---	-------------------------------------

Datasheet

②	Four 1000BASE-X ports
③	One console port
④	One USB port
⑤	One RST button

The Back Panel:



⑥	Ground screw
⑦	Jack for AC power cable locking strap
⑧	AC socket

Get more information:

Do you have any question about the S1730S-S48P4S-A1 98011347?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Part Number	98011347
Model	S1730S-S48P4S-A1
Description	S1730S-S48P4S-A1 (48*10/100/1000BASE-T ports, 4*GE SFP ports, PoE+, AC power)
First supported version	V200R020C10
Dimensions without packaging (H x W x D) [mm(in.)]	Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 220.0 mm (1.72 in. x 17.4 in. x 8.7 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 227.0 mm (1.72 in. x 17.4 in. x 8.94 in.)
Dimensions with packaging (H x W x D) [mm(in.)]	90.0 mm x 550.0 mm x 360.0 mm (3.54 in. x 21.65 in. x 14.17 in.)
Chassis height [U]	1 U
Weight without packaging [kg(lb)]	3.23 kg (7.12 lb)
Weight with packaging [kg(lb)]	4.28 kg (9.44 lb)
Typical power consumption [W]	58.7 W
Typical heat dissipation [BTU/hour]	200.29 BTU/hour
Maximum power consumption [W]	Not providing the PoE function: 76.1 W 100% PoE loads: 456.1 W (PoE: 380 W)
Maximum heat dissipation [BTU/hour]	Not providing the PoE function: 259.66

Datasheet

	100% PoE loads: 1556.26
MTBF [year]	44.9 year
MTTR [hour]	2 hour
Availability	>0.99999
Noise at normal temperature (acoustic power) [dB(A)]	50 dB(A)
Noise at normal temperature (acoustic pressure) [dB(A)]	38.2 dB(A)
Number of card slots	0
Number of power slots	0
Number of fans modules	2
Redundant power supply	Not supported
Long-term operating temperature [°C(°F)]	-5°C to +50°C (23°F to 122°F) at an altitude of 0-1800 m (0-5906 ft.)
Short-term operating temperature [°C(°F)]	-5°C to +55°C (23°F to 131°F) at an altitude of 0-1800 m (0-5906 ft.)
Restriction on the operating temperature variation rate [°C(°F)]	<p>When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.).</p> <p>The equipment can operate beyond the normal operating temperature range for a short-term period, but the following conditions must be met:</p> <ul style="list-style-type: none"> ● The equipment operates at a temperature of over 50°C (122°F) consecutively for at most 96 hours in one year. ● The equipment operates at a temperature of over 50°C (122°F) for a total of no more than 360 hours in one year. ● The equipment operates at a temperature of over 50°C (122°F) for no more in 15 times in one year. <p>The equipment may be damaged or experience unexpected exceptions if any of the preceding limits is exceeded.</p> <p>The equipment cannot start when the temperature is lower than 0°C (32°F). The maximum distance of optical modules used in these conditions cannot exceed 10 km.</p>
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% to 95%, noncondensing
Long-term operating altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Storage altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Power supply mode	AC built-in
Rated input voltage [V]	AC input: 100 V AC to 240 V AC, 50/60 Hz High-Voltage DC input: 240 V DC
Input voltage range [V]	AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz High-Voltage DC input: 190 V DC to 290 V DC
Maximum input current [A]	6 A
Memory	512 MB
Flash memory	512 MB
Console port	RJ45

Datasheet

Eth Management port	Not supported
USB	Supported
RTC	Not supported
RPS input	Not supported
Service port surge protection [kV]	Common mode: ± 7 kV
Power supply surge protection [kV]	± 6 kV in differential mode, ± 6 kV in common mode
Types of fans	Built-in
Heat dissipation mode	Heat dissipation with fan, intelligent fan speed adjustment
Airflow direction	Air intake from left and front, air exhaustion from right
PoE	Supported
Certification	EMC certification Safety certification Manufacturing certification

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

