

## Datasheet

[Get a Quote](#)

## Overview

Huawei ME60 50G Flexible Card Broadband Service Unit(BSUF-51,2 sub-slots)

### Quick Specification

Model	ME0DBSUF5170
Part Number	3054629
Description	Flexible Card Broadband Service Unit(BSUF-51,2 sub-slots)
Attributes	Hardware
Dimensions (mm)	40.1(H)x 399.2(W) x 535.6(D)
Weight(kg)	7.15
Power consumption (typical value) (W)	180

## Product Details:

### Huawei ME0DBSUF5170

Huawei ME60 50G flexible broadband service board (BSUF-51,2 sub-slots).

Provides two 1/2-width slots, and each slot holds one FPIC.

FPIC supports Hot swap, Automatic recovery of configurations and Intermixing with other types of FPICs.

Huawei ME0DBSUF5170 is a flexible broadband service board (BSUF-51,2 sub-slots) applied to Huawei ME60, enhances networking flexibility and provides low-cost and customized solutions supports packet forwarding at the line speed of 50 Gbit/s, also provides two 1/2-width slots, and each slot holds one FPIC.

ME0DBSUF5170 comes with original box, if purchase together with router, it will be will inserted into the router by default when delivery, to economical volume weight; If need delivery separately with original box, please contact Thunder-link.com sales team in advance.

## Datasheet

### The Front Panel:



### The Accessories for ME0DBSUF5170

#### Mapping products and versions

Product	Minimum Version Requirement
ME60-X3	V800R008C10
ME60-X8	V800R008C10
ME60-X16	V800R008C10
ME60-X8A	V800R008C10
ME60-X16A	V800R008C10

Get more information:

Do you have any question about the ME0DBSUF5170 03054629?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

### Specific Data Sheet:

Part Number	03054629
Model	ME0DBSUF5170
Description	Flexible Card Broadband Service Unit(BSUF-51,2 sub-slots)
Attributes	Hardware
List Price(USD)	90,000.00
Category	Line Card
Product Line	Networking
Product Family	Router

## Datasheet

Overview	Line Card
Product Series	ME60-X8
UOM	PCS
Net Dimension (D*W*H mm)	532*399*40
Typic Power(W)	198
Reliability and availability	Software features Nonstop Forwarding (NSF) MPLS Fast Reroute (FRR) Hardware features The BSUF-51 supports hot swap. The FPIC of the BSUF-51 supports hot swap
NMS	Enhanced command-line interface SNMP and MIB support
Operating conditions	Long-term ambient temperature: 0°C to 45°C (32°F to 113°F) Short-term ambient temperature: -5°C to +55°C (23°F to 131°F) Long-term relative humidity: 5% to 85% Short-term relative humidity: 5% to 95%
Storage conditions	Storage temperature: -40°C to +70°C (-40°F to 158°F) Storage humidity: 5% to 100%

## Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

 Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

 Email: [info@hi-network.com](mailto:info@hi-network.com)

 Skype: [echo.hinetwork](https://www.skype.com/addtocontactlist/echo.hinetwork)

WhatsApp Business: +8618057156223