

## Datasheet

[Get a Quote](#)

## Overview

Huawei AR G3 AR150 Series - AR157 fixed interface access enterprise router AR0M1570BA00 provides routing and switching functionality for small business or branch offices

## Quick Specification

Model	AR207
Part Number	02353841
Memory	512 MB
Flash	512 MB
Micro SD card (default: sd1)	None
Hard disk	Not supported
LAN Ports	8 port(s) x RJ-45
WAN Ports	1 port(s) x
USB Ports	1 x USB
Weight(kg)	2.8
Dimensions (W x D x H)	4.45cm (W) x 30.0cm (D) x 22.0cm (H)

## Datasheet

### Product Details:

#### The Front Panel:



#### The Back Panel:



Get more information:

Do you have any question about the AR207 02353841?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

### Specific Data Sheet:

Part Number	02353841
Model	AR207
First Supported Version	V200R002C00

## Datasheet

Memory Size	512 MB
Flash Memory	512 MB
Basic feature	DHCP server/client, PPPoE server/client, PPPoA server/client, PPPoEoA server/client, NAT, Sub interface management
Voice	RTP, SIP, SIP AG, IP PBX/TDM PBX, FXO/FXS, VoIP/conference call, BEST, DISA, SBC, (Only voice models support voice features)
WLAN(AP)	AP management, WLAN QoS, WLAN security, WLAN radio management, WLAN user management(Only WLAN models support WLAN AP features)
WLAN(AC)	AP management(AC discovery/AP access/AP management),CAPWAP,WLAN user management , WLAN radio management ( 802.11a/b/g/n ) ,WLAN QoS ( WMM), WLAN security ( WEP/WPA/WPA2/Key management )
LAN	IEEE 802.1P, IEEE 802.1Q, IEEE 802.3, VL AN management, MAC address management, MSTP
IPv4 unicast routing	Routing policy, static route, RIP, OSPF, IS-IS, BGP
IPv6 unicast routing	Routing policy, static route, RIPng, OSPFv3, IS-ISv6, BGP4+
Multicast	IGMP version1/2/3, PIM SM, PIM DM, MSDP
MPLS	LDP, MPLS L3 VPN, VLL, PWE3, static LSP, dynamic LSP, MPLS TE, IP FRR, LDP FRR, TE FRR
VPN	IPSec VPN, GRE VPN, DSVPN, L2TP VPN, Smart VPN
QoS	DiffServ mode, MPLS QoS, priority mapping, traffic policing (CAR), traffic shaping, congestion avoidance (based on IP precedence/DSCP WRED), congestion management (LAN interface: SP/WRR/SP+WRR; WAN interface: PQ/CBWFQ), MQC (traffic classifier, traffic behavior, and traffic policy), Hierarchical QoS, WLAN QoS, FR QoS, Smart Application Control (SAC)
Security	ACL, firewall, 802.1x authentication, AAA authentication, RADIUS authentication, HWTACACS authentication, broadcast storm suppression, ARP security, ICMP attack defense, URPF, CPCAR, blacklist, IP source tracing, PKI.
Management and maintenance	Upgrade management, device management, web-based GUI, GTL, SNMP(v1/v2c/v3), RMON, NTP, CWMP, Auto-Config, site deployment using USB disk, CLI
Maximum power consumption(W)	36
Operating temperature	0°C to 45°C
Operating relative humidity	5% to 95%, noncondensing
Dimensions(mm)	44.5 (H) x 300 (W) x 220 (D)

## Want to Buy

[Get a Quote](#)


AR207 (02353841)

## Datasheet



**HI-NETWORK.com**  
Your Global Original Network Supplier

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

---

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

