

[Get a Quote](#)

Overview

Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1511nm, 70km, LC)

Quick Specification

Table 1 shows the Quick Specs.

Model	SFP-10G-ZCW1511
Part Number	02310SSE
Description	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1511nm, 70km, LC)
Level-1 category	10GE-CWDM SFP+ Optical Modules
Connector type	LC
Optical fiber type	SMF
Form factor	SFP+
Transmission rate [bit/s]	10 Gbit/s
Target transmission distance [km]	Single-mode fiber: 70 km
Application standard	10G-CWDM
Working case temperature [°C(°F)]	0°C to 70°C (32°F to 158°F)
Center wavelength [nm]	1511
Maximum Tx optical power [dBm]	4.0
Minimum Tx optical power [dBm]	0
Overload power [dBm]	-7.0
Minimum extinction ratio [dB]	8.2
Rx sensitivity [dBm]	-23.0

Figure 1 shows the appearance.



Get More Information

Do you have any question about the SFP-10G-ZCW1511 (02310SSE)?

Contact us now via info@hi-network.com.

Specification

SFP-10G-ZCW1511 Specification	
Basic Information	
Model	SFP-10G-ZCW1511
Part Number	02310SSE
Description	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1511nm, 70km, LC)
Level-1 category	10GE-CWDM SFP+ Optical Modules
Form factor	SFP+
Application standard	10G-CWDM
Connector type	LC
Optical fiber type	SMF
Working case temperature [°C(°F)]	0°C to 70°C (32°F to 158°F)
Transmission rate [bit/s]	10 Gbit/s
Target transmission distance [km]	Single-mode fiber: 70 km
Transmitter Optical Characteristics	
Center wavelength [nm]	1511
Maximum Tx optical power [dBm]	4.0
Minimum Tx optical power [dBm]	0
Minimum extinction ratio [dB]	8.2
Receiver Optical Characteristics	
Rx sensitivity [dBm]	-23.0
Overload power [dBm]	-7.0

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223