SFP-10G-AC10M (02310MUQ)

Datasheet



Get a Quote

Overview

The 10G SFP+ Active Direct Attach Copper Twinax Cable is designed for use in 10GBASE Ethernet. This cable is compliant with IEEE 802.3, SFF-8431, and SFP+ MSA. With these features, this easy to install, high speed, cost-effective direct attach copper twinax cable is suitable for short-distance connectivity within a rack or between adjacent racks in data centers.

Quick Specification

Table 1 shows the Quick Specification.

Model	SFP-10G-AC10M
Part Number	02310MUQ
Description	SFP+, 10G, Active High Speed Cables, 10m, SFP+20M, CC2P0.32B(S), SFP+20M, Used indoor
Connector X1	SFP+
Connector X2	SFP+
Cable length [m (ft.)]	10 m (32.81 ft.)
Electrical attribute	Active
Bend radius [mm (in.)]	25 mm (0.98 in.)
Minimum Clearance for Cable Routing [mm (in.)]	60 mm (2.36 in.)

Figure 1 shows the appearance of SFP-10G-AC10M.



Get More Information

Do you have any question about the SFP-10G-AC10M (02310MUQ)?

Contact us now via info@hi-network.com.



SFP-10G-AC10M (02310MUQ)

Datasheet



Specification

SFP-10G-AC10M Specification	
Model	SFP-10G-AC10M
Part Number	02310MUQ
Description	SFP+, 10G, Active High Speed Cables, 10m, SFP+20M, CC2P0.32B(S), SFP+20M, Used indoor
Attributes	Hardware
Category	Optical Transceiver
Product Line	Networking
Product Family	Switch
Product Category	Optical Transceiver
Sub Product Family	Campus Switch
Product Series	S7700
EAN	6920702752592
UOM	PCS
Pack Weight(kg)	1.17
Pack Volume(m^3)	0.008
Pack Dimension (D*W*H mm)	338*251*90
Net Dimension (D*W*H mm)	338*251*90

Want to Buy

Get a Quote









<u>Learn More</u> about Hi-Network

Search our Resource Library

 \underline{Follow} us on LinkedIn

Contact for Sales or Support



SFP-10G-AC10M (02310MUQ)

Datasheet



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601 HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com Skype: echo.hinetwork

WhatsApp Business: +8618057156223

