

Get a Quote

Overview

SMF, 1550nm-RX, 40km, LC

Quick Specification

Table 1 shows the Quick Specs.

Model	SFP-GE-LH40-SM1550
Part Number	02317347
Transceiver form factor	eSFP
Transmission speed	1 Gbit/s
Center wavelength (nm)	1550
Standard compliance	1000base-LX/LH
Connector type	LC
Applicable cable and maximum transmission distance	Single-mode fiber: 40 km
Transmit power (dBm)	-5.0 to 0
Maximum receiver sensitivity (dBm)	-22
Overload power (dBm)	-3
Extinction ratio (dB)	8.5
Operating temperature	0°C to 70°C (32°F to 158°F)
Net Dimension (D x W x H mm)	110 x 70 x 37

Figure 1 shows the appearance.



The Supported Switches

Table 2 shows the Huawei hot switches which support S-SFP-GE-LH40-SM1550.

Model	Description
S5700-28P-LI-AC	24 x Ethernet 10/100/1000 ports, 4 Gig SFP, AC 110/220V
S5700-28TP-LI-AC	24 x Ethernet 10/100/1000ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP, AC



	110/220V
S5700S-52P-LI-AC	48 x Ethernet 10/100/1000 ports, 4 Gig SFP, AC 110/220V
S5700-28P-PWR-LI-AC	24 x Ethernet 10/100/1000 PoE+ ports, 4 Gig SFP, AC 110/220V
S5700-10P-PWR-LI-AC	8 x Ethernet 10/100/1000 PoE+ ports, 2 Gig SFP, AC 110/220V
S5720-36C-EI-AC	28 x Ethernet 10/100/1000 ports, 4 of which are dual-purpose 10/100/1000 or SFP,
	4 10 Gig SFP+, 1 interface slot, with 150W AC
S5700-28C-EI-AC	24 x Ethernet 10/100/1000 ports, with 1 interface slot, with 150W AC power supply
S5720-56C-HI-AC	48 x Ethernet 10/100/1000 ports, 4 10 Gig SFP+, with 2 interface slots, with 600W AC power supply
S5720-56PC-EI-AC	48 x Ethernet 10/100/1000 ports, 4 Gig SFP, with 1 interface slot, with 150W AC power supply
S5720-56C-PWR-HI-AC	48 x Ethernet 10/100/1000 POE+ ports, 4 10 Gig SFP+, with 2 interface slots, with 1150W AC power supply

Compare to Similar Items

Table 3 shows the comparison of S-SFP-GE-LH40-SM1310 and S-SFP-GE-LH40-SM1550.

Item	S-SFP-GE-LH40-SM1310	S-SFP-GE-LH40-SM1550
Transceiver form factor	eSFP	eSFP
Transmission speed	1 Gbit/s	1 Gbit/s
Center wavelength (nm)	1310	1550
Standard compliance	1000base-LX/LH	1000base-LX/LH
Connector type	LC	LC
Applicable cable and maximum transmission distance	Single-mode fiber: 40 km	Single-mode fiber: 40 km
Transmit power (dBm)	-5.0 to 0	-5.0 to 0
Maximum receiver sensitivity (dBm)	-23	-22
Overload power (dBm)	-3	-3
Extinction ratio (dB)	9	8.5
Operating temperature	0°C to 70°C (32°F to 158°F)	0°C to 70°C (32°F to 158°F)
Net Dimension (D x W x H mm)	110 x 70 x 37	110 x 70 x 37

Get more information:

Do you have any question about the SFP-GE-LH40-SM1550(02317347)?

Contact us now via email: info@hi-network.com

Specification:

S-SFP-GE-LH40-SM1550 Specification	
Transceiver form factor	eSFP
Transmission speed	1 Gbit/s



Center wavelength (nm)	1550
Standard compliance	1000base-LX/LH
Connector type	LC
Applicable cable and maximum transmission distance	Single-mode fiber: 40 km
Transmit power (dBm)	-5.0 to 0
Maximum receiver sensitivity (dBm)	-22
Overload power (dBm)	-3
Extinction ratio (dB)	8.5
Operating temperature	0°C to 70°C (32°F to 158°F)
Net Dimension (D x W x H mm)	110 x 70 x 37

Want to Buy

[Get a Quote](#)[Learn More](#) about Hi-Network[Search](#) our Resource Library[Follow](#) us on LinkedInContact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

