

[Get a Quote](#)

Overview

Huawei OSX010000 is a 10G Optical Transceiver. It's a Single-mode Module.

Quick Specification

Table 1 shows the Quick Specification.

Model	OSX010000
Part Number	02313URK 02318170
Transceiver form factor	SFP+
Transmission speed	10 Gbit/s
Center wavelength (nm)	1310
Standard compliance	10Gbase-LR
Connector type	LC
Applicable cable and maximum transmission distance	Single-mode fiber: 10 km
Transmit power (dBm)	-8.2 to +0.5
Maximum receiver sensitivity (dBm)	-12.6
Overload power (dBm)	0.5
Extinction ratio (dB)	3.5
Operating temperature	0°C to 70°C (32°F to 158°F)
Net Dimension (D x W x H mm)	110 x 70 x 3

Figure 1 shows the appearance.

OSX010000 can be installed in the switch's SFP slot.



Product Details

The Supported Switches

Table 2 shows the Huawei hot switches which support OSX010000.

Model	Description
S5700-28P-LI-AC	24 x Ethernet 10/100/1000 ports, 4 Gig SFP, AC 110/220V
S5700-28TP-LI-AC	24 x Ethernet 10/100/1000ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP, AC 110/220V
S5700S-52P-LI-AC	48 x Ethernet 10/100/1000 ports, 4 Gig SFP, AC 110/220V
S5700-28P-PWR-LI-AC	24 x Ethernet 10/100/1000 PoE+ ports, 4 Gig SFP, AC 110/220V
S5700-10P-PWR-LI-AC	8 x Ethernet 10/100/1000 PoE+ ports, 2 Gig SFP, AC 110/220V
S5720-36C-EI-AC	28 x Ethernet 10/100/1000 ports,4 of which are dual-purpose 10/100/1000 or SFP,4 10 Gig SFP+, 1 interface slot, with 150W AC
S5700-28C-EI-AC	24 x Ethernet 10/100/1000 ports, with 1 interface slot, with 150W AC power supply
S5720-56C-HI-AC	48 x Ethernet 10/100/1000 ports, 4 10 Gig SFP+, with 2 interface slots, with 600W AC power supply
S5720-56PC-EI-AC	48 x Ethernet 10/100/1000 ports,4 Gig SFP, with 1 interface slot, with 150W AC power supply
S5720-56C-PWR-HI-AC	48 x Ethernet 10/100/1000 POE+ ports,4 10 Gig SFP+, with 2 interface slots, with 1150W AC power supply

Compare to Similar Items

Table 3 shows the comparison of OSX010000 and OMXD30000.

Item	OSX010000	OMXD30000
Transceiver form factor	SFP+	SFP+
Transmission speed	10 Gbit/s	10 Gbit/s
Center wavelength (nm)	1310	1310
Standard compliance	10Gbase-LR	10GBASE-iLR
Connector type	LC	LC
Applicable cable and maximum transmission distance	Single-mode fiber: 10 km	Single-mode fiber: 1.4 km
Transmit power (dBm)	-8.2 to +0.5	-8.2 to +0.5
Maximum receiver sensitivity (dBm)	-12.6	-14.4
Overload power (dBm)	0.5	0.5
Extinction ratio (dB)	3.5	3.5
Operating temperature	0°C to 70°C (32°F to 158°F)	-40°C to +85°C (-40°F to +185°F)

Get More Information

Do you have any question about the OSX010000 (02313URK 02318170)?

Contact us now via info@hi-network.com.

Specification

OSX010000 Specification	
Model	OSX010000
Part Number	02313URK 02318170
Form factor	SFP+
Application standard	10GBASE-LR
Connector type	LC
Optical fiber type	SMF
Working case temperature [°C(°F)]	0°C to 70°C (32°F to 158°F)
Transmission rate [bit/s]	10 Gbit/s
Target transmission distance [km]	Single-mode fiber: 10 km
Center wavelength [nm]	1310 nm
Maximum Tx optical power [dBm]	0.5 dBm
Minimum Tx optical power [dBm]	-8.2 dBm
Minimum extinction ratio [dB]	3.5 dB
Rx sensitivity [dBm]	-12.6 dBm
Overload power [dBm]	0.5 dBm

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

OSX010000 (02313URK 02318170)

Datasheet



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223