EH1D2SRUC000 (03021UWG)

Datasheet

HI-NETWORK.com

Get a Quote

Overview

The EH1D2SRUC000 integrates control and switching functions and provides the control plane, management plane, and data plane for the system. This card provides a clock daughter card slot.

Quick Specification

Table 1 shows the quick specification.

Model	EH1D2SRUC000
Part Number	03021UWG
Description	S9706/S9712 Main Control Unit C (Optional Clock)
Level-1 category	MPU
Dimensions (H x W x D) [mm(in.)]	394.7 mm x 426.8 mm x 35.1 mm (5.7 in. x 7.3 in. x 0.8 in.)
Weight [kg(lb)]	3.30 kg (7.28 lb)
Maximum power consumption [W]	132 W (including subcards)
Environmental Parameters	Operating temperature: 0°C to 45°C (32°F to 113°F)
	Operating relative humidity: 5% RH to 95% RH (noncondensing)
	Storage temperature: -40°C to +70°C (-40°F to +158°F)
	Storage relative humidity: 5% RH to 95% RH (noncondensing)

Figure 1 shows the appearance of EH1D2SRUC000.



Get More Information

Do you have any question about the EH1D2SRUC000 (03021UWG)?

Contact us now via info@hi-network.com.



EH1D2SRUC000 (03021UWG)

Datasheet



Specification

EH1D2SRUC000 Specification Basic Information	
Part Number	03021UWG
Description	S9706/S9712 Main Control Unit C (Optional Clock)
Level-1 category	MPU
Technical Specifications	
Dimensions (H x W x D) [mm(in.)]	394.7 mm x 426.8 mm x 35.1 mm (5.7 in. x 7.3 in. x 0.8 in.)
Weight [kg(lb)]	3.30 kg (7.28 lb)
Maximum power consumption [W]	132 W (including subcards)
Environmental Parameters	Operating temperature: 0°C to 45°C (32°F to 113°F)
	Operating relative humidity: 5% RH to 95% RH (noncondensing)
	Storage temperature: -40°C to +70°C (-40°F to +158°F)
	Storage relative humidity: 5% RH to 95% RH (noncondensing)

Want to Buy



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601 HangZhou Office Tel: +0086-571-86729517 Email: info@hi-network.com Skype: echo.hinetwork WhatsApp Business: +8618057156223

