

[Get a Quote](#)

## Overview

The Cisco XFP module offers customers a variety of 10 Gigabit Ethernet and Packet-over-SONET/SDH (POS) connectivity options for data center, enterprise wiring closet, and service provider transport applications.

## Quick Specification

|                             |                                                                          |
|-----------------------------|--------------------------------------------------------------------------|
| Product Code                | XFP-10GER-192IR+                                                         |
| Description                 | Cisco Multirate 10GBASE-ER/-EW and OC-192/STM-64 IR-2 XFP Module for SMF |
| Operating Temperature Range | COM                                                                      |
| Power Consumption (W)       | 3.5                                                                      |

## Product Details:

### The Front Panel:



## Compare to Similar Items:

|              |                                                                               |                                                                          |
|--------------|-------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| Product Code | <a href="#">XFP10GER-192IR-L</a>                                              | <a href="#">XFP10GER-192IR+</a>                                          |
| Description  | Cisco Multirate 10GBASE-ER/-EW and OC-192/STM-64 IR-2 XFP Module for SMF, low | Cisco Multirate 10GBASE-ER/-EW and OC-192/STM-64 IR-2 XFP Module for SMF |



|                             |              |     |
|-----------------------------|--------------|-----|
|                             | power (2.5W) |     |
| Operating Temperature Range | COM          | COM |
| Power Consumption (W)       | 2.5          | 3.5 |

Get more information:

Do you have any question about the XFP-10GER-192IR+?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

## Specific Data Sheet:

|                               |                                                         |
|-------------------------------|---------------------------------------------------------|
| Product Code                  | XFP-10GER-192IR+                                        |
| Device Type                   | XFP transceiver module                                  |
| Form Factor                   | Plug-in module                                          |
| Connectivity Technology       | Wired                                                   |
| Cabling Type                  | 10GBase-ER, 10GBase-EW                                  |
| Data Link Protocol            | SONET/SDH, 10 GigE                                      |
| Data Transfer Rate            | 10 Gbps                                                 |
| Optical Wave Length           | 1550 nm                                                 |
| Line Rate                     | OC-192/STM-64                                           |
| Max Transfer Distance         | 24.9 miles                                              |
| Features                      | PoS (Packet over SONET)                                 |
| Compliant Standards           | IEEE 802.3ae                                            |
| Interfaces                    | 1 x Ethernet 10GBase-ER/10GBase-EW - LC single-mode x 2 |
| Compatible Slots              | 1 x XFP                                                 |
| Compliant Standards           | Laser Class 1, IEC 60825-1                              |
| Power Consumption Operational | 3.5 Watt                                                |
| Width                         | 0.7 in                                                  |
| Depth                         | 2.8 in                                                  |
| Height                        | 0.3 in                                                  |
| Weight                        | 10.58 oz                                                |
| Min Operating Temperature     | 32 °F                                                   |
| Max Operating Temperature     | 158 °F                                                  |



## Want to Buy

---

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

---

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: [echo.hinetwork](#)

WhatsApp Business: +8618057156223