

Get a Quote

Overview

The Cisco IP Phone 7841 delivers advanced IP Telephony features and crystal-clear wideband audio performance to deliver an easy-to-use, full-featured voice communications experience on Cisco on-premises and hosted infrastructure platforms and third party hosted call control.

Quick Specs

Figure 1 shows the appearance of the CP-7841-K9.



Table 1 shows the Quick Spec.

Product Code	CP-7841-K9
Screen	396 x 162 pixel (3.5 in. / 89 mm)
Ethernet Switch	10/100/1000
Programmable Line Keys	4
Full Duplex Speakerphone	Yes
Number of Line Keys	4
Wideband Audio	Yes
PoE Class	1

Third-party Call Control	Yes
Replaceable Bezel	Yes
Package Weight	1.6 Kg

Product Details

Before you use the Cisco IP Phone 7841, it should be connected to the corporate IP telephony network.

Figure 2 shows the bottom ports of this IP Phone.



Note:

(1)	AC power wall plug (optional)	(4)	Auxiliary port (optional)
(2)	Network port (10/100 SW) connection. IEEE 802.3af power enabled	(5)	Handset connection
(3)	Access port (10/100 PC) connection	(6)	Analog headset connection (optional)

Figure 3 shows the buttons and hardware.



Note:

(1)	Handset light strip	(10)	Headset button
(2)	Programmable feature buttons	(11)	Mute button
(3)	Phone screen	(12)	Keypad
(4)	Softkey buttons	(13)	Volume button
(5)	Navigation and Select button	(14)	Contacts button
(6)	Hold/Resume button	(15)	Applications button
(7)	Conference button	(16)	Messages button
(8)	Transfer button	(17)	Handset
(9)	Speakerphone button		

Get More Information

Do you have any question about the Cisco IP Phone 7841/K9?

Contact us now via info@hi-network.com.

Specification

CP-7841-K9 Specification

<p>Signaling protocol support</p>	<ul style="list-style-type: none"> • Session Initiation Protocol (SIP)
<p>Codec support</p>	<ul style="list-style-type: none"> • G.711a/μ, G.722, G.729a, iLBC
<p>Key call features support</p>	<ul style="list-style-type: none"> • + Dialing (E.164) • Abbreviated dial • Adjustable ringing and volume levels • Adjustable display contrast • Agent greeting • Auto-answer • Auto-detection of headset (Not available on the IP Phone 7811) • Busy Lamp Field (BLF) (Not available on the IP Phone 7811) • Call back • Call forward • Call history • Call park • Call Pickup • Call timer • Call waiting • Caller ID • cBarge • Corporate directory • Conference • Cross Cluster Extension Mobility (EMCC) • Dial from the list • Direct transfer • Do not disturb • Extension Mobility (EM) • Forced access codes and client matter codes • Group call pickup • Hold/resume • Immediate divert • Intercom (Not available on the IP Phone 7811) • Join (Not available on the IP Phone 7811) • Message-waiting indicator • Meet me conference • Mobility • Music on hold • Mute • Network profiles (automatic) • On- and off-network distinctive ringing • Personal directory • Privacy • Private Line Automated Ringdown (PLAR) • Redial • Ring tone per line appearance • Shared line



	<ul style="list-style-type: none"> ● Silent monitoring and recording ● Speed dial ● Time and date display ● Transfer ● Voicemail ● Whisper coaching
<p>Language support</p>	<ul style="list-style-type: none"> ● Arabic (Arabic Area) ● Bulgarian (Bulgaria) ● Catalan (Spain) ● Chinese (China) ● Chinese (Hong Kong) ● Chinese (Taiwan) ● Croatian (Croatia) ● Czech (Czech Republic) ● Danish (Denmark) ● Dutch (Netherlands) ● English (United Kingdom) ● Estonian (Estonia) ● French (France) ● Finnish (Finland) ● German (Germany) ● Greek (Greece) ● Hebrew (Israel) ● Hungarian (Hungary) ● Italian (Italy) ● Japanese (Japan) ● Latvian (Latvia) ● Lithuanian (Lithuania) ● Korean (Korea Republic) ● Norwegian (Norway) ● Polish (Poland) ● Portuguese (Portugal) ● Portuguese (Brazil) ● Romanian (Romania) ● Russian (Russian Federation) ● Spanish (Columbia) ● Spanish (Spain) ● Slovak (Slovakia) ● Swedish (Sweden) ● Serbian (Republic of Serbia) ● Serbian (Republic of Montenegro) ● Slovenian (Slovenia) ● Thai (Thailand) ● Turkish (Turkey)
<p>Multiple ring tones</p>	<ul style="list-style-type: none"> ● The phone supports user-adjustable ring tones.
<p>Directories</p>	<ul style="list-style-type: none"> ● The phone identifies incoming messages and categorizes them for users on the screen. This makes it fast and





	easy to return calls using direct dial-back capability. The corporate directory integrates with the Lightweight Directory Access Protocol (LDAP) standard directory.
Quality-of-service (QoS) options	<ul style="list-style-type: none"> • The phone supports CDP and 802.1Q/p standards, and can be configured with an 801.1Q VLAN header containing the VLAN ID overrides configured by the Admin VLAN ID.
Security	<ul style="list-style-type: none"> • Certificates • Image authentication • Device authentication • File authentication • Signaling authentication • Media encryption using Secure Real-Time Transfer Protocol (SRTP) using AES-128 • Signaling encryption using Transport Layer Security (TLS) Protocol using AES-128 or AES-256 • Encrypted configuration files • 802.1X authentication • Cryptography
Configuration options	<ul style="list-style-type: none"> • The user can configure IP address assignment statically or through the DHCP client.
Physical dimensions (H×W×D)	<ul style="list-style-type: none"> • IP Phone 7841: 207 x 206 x 28mm (exclude foot stand)
Weight	<ul style="list-style-type: none"> • IP Phone 7841: 868g
Display	<ul style="list-style-type: none"> • IP Phone 7841: 3.5" 396×162 pixels
Ethernet switch	<ul style="list-style-type: none"> • The phone has a 10/100BASE-T or a 10/100/1000BASE-T (The Cisco® IP Phone 7841) Ethernet connection through two RJ-45 ports, one for the LAN connection and the other for a downstream Ethernet device connection like a PC.
Phone casing composition	<ul style="list-style-type: none"> • Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic.
Power requirements	<ul style="list-style-type: none"> • The phone is an interoperable IEEE 802.3af PoE (Class 1 device); 48 VDC is required; it can be supplied locally at the desktop using an optional AC-to-DC power supply (CP-PWR-CUBE-3=). Use of the power supply also requires the use of one of the corresponding AC country cords.
Operational temperature	<ul style="list-style-type: none"> • 32 to 104°F (0 to 40°C)
Nonoperational temperature shock	<ul style="list-style-type: none"> • 14 to 140°F (-10 to 60°C)
Humidity	<ul style="list-style-type: none"> • Operating 10% to 90%, non-condensing • Non-operating 10% to 95%, non-condensing
Cosmetic	<ul style="list-style-type: none"> • Cisco cosmetic class A
Certification and compliance	<ul style="list-style-type: none"> • Regulatory Compliance <ul style="list-style-type: none"> ◦ CE Markings per directives 2004/108/EC and 2006/95/EC • Safety <ul style="list-style-type: none"> ◦ UL 60950 Second Edition ◦ CAN/CSA-C22.2 No. 60950 Second Edition ◦ EN 60950 Second Edition (including A11 & A12) ◦ IEC 60950 Second Edition (including A11 & A12) ◦ AS/NZS 60950 ◦ GB4943 • EMC - Emissions <ul style="list-style-type: none"> ◦ 47CFR Part 15 (CFR 47) Class B ◦ AS/NZS CISPR22 Class B ◦ CISPR22: 2005 w/Amendment 1: 2005 Class B ◦ EN55022: 2006 w/Amendment 1: 2007 Class B



- ICES003 Class B
- VCCI Class B
- EN61000-3-2
- EN61000-3-3
- KN22 Class B
- EMC - Immunity
- EN55024
- CISPR24
- EN60601-1-2
- KN24
- Armadillo Light
- Telecom
- FCC Part 68 HAC
- CS-03-HAC
- AS/ACIF S004
- AS/ACIF S040
- NZ PTC 220
- Industry Standards: TIA 810 and TIA 920
- Industry Standards: IEEE 802.3 Ethernet, IEEE 802.3af and 802.3at

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

