

Get a Quote

## Overview

Cisco® Unified Communications Solutions unify voice, video, data, and mobile applications on fixed and mobile networks, delivering a media-rich collaboration experience across business, government agency, and institutional workspaces. These applications use the network as the platform to enhance comparative advantage by accelerating decision time and reducing transaction time. The security, resilience, and scalability of the network enable users in any workspace to easily connect anywhere, anytime, and anyplace, using any media, device or operating system. Cisco Unified Communications is part of a comprehensive solution that includes network infrastructure, security, wireless, management applications, lifecycle services, flexible deployment and outsourced management options, and third-party applications. The Cisco Unified IP Phone 7962G (Figure 1) is a full-featured IP phone with speakerphone and handset designed for wideband audio. It is intended to meet the needs of managers and administrative assistants. It has six programmable backlit line/feature buttons and four interactive soft keys that guide you through all call features and functions. The phone has a large, 4-bit grayscale graphical LCD (Figure 2) that provides features such as date and time, calling party name, calling party number, digits dialed, and presence information. The crisp graphic capability of the display allows for the inclusion of higher value, more visibly rich Extensible Markup Language (XML) applications, and support for localization requiring double-byte Unicode encoding for fonts. A hands-free speakerphone and handset designed for hi-fidelity wideband audio are standard on the Cisco Unified IP Phone 7962G, as is a built-in headset connection and an integrated Ethernet switch.

## Quick Specification

Figure 1 shows the Cisco Unified IP Phone 7962G.



Figure 2 shows the Close-Up of Display and Lighted Line Keys.



Table 1 shows the quick specification.

Specification	Description
Dimensions (H x W x D)	8.2 x 10.5 x 6 in. (20.32 x 26.67 x 15.24 cm)
Weight	3.5 lb (1.6 kg)
Phone-Casing Composition	Acrylonitrile butadiene styrene (ABS) plastic in textured dark gray color with silver bezel
Power	Supports IEEE 802.3af PoE (Class 2). Also supports Cisco Prestandard Power over Ethernet (PoE), allowing powering from any of the Cisco Inline Power-capable blades and boxes, plus Cisco midspan. 48VDC is required; it can be supplied locally at the desktop using an optional AC-to-DC power supply (part number CP-PWR-CUBE-3=) or power injector (CP-PWR-INJ=). Local power options require a corresponding AC country cord (see Table 6).
Phone Software Requirements	Supported in 8.3(2) and greater
Call Control compatibility	Supported in Cisco Unified Communications Manager Versions 4.1(3) sr5b, 4.2(3) sr2b, 4.3(1), 5.1.1(b), 5.1(2), 6.0(1) and greater Supported in Cisco Unified Communications Express and SRST Version 4.1
Signaling Protocols	Skippy Client Control Protocol (SCCP) and Session Initiation Protocol (SIP) with Cisco call control

## Product Details

The Cisco Unified IP Phone 7962G is designed to grow with your organization and enhancements to your system capabilities. The dynamic feature set allows the phone to keep pace with your requirements through regular software updates. Firmware changes can be downloaded from Cisco.com. No hands-on moves and changes are required with the phone-you can simply pick up the phone and move to a new location anywhere on your network. The Cisco Unified IP Phone 7962G also provides many accessibility features. Table 2 lists the phone's features.

Table 2 shows the Cisco Unified IP Phone 7962G Features.

Feature	Description/Benefit
Display	5-inch (12.5 cm), high-resolution (320 x 222), graphical monochrome 4-bit grayscale display. Allows for greater flexibility of features and applications, and significantly expands the information viewed when using features such as Services, Information, Messages, and Directory. Display also supports localization requiring double-byte Unicode encoding for fonts.
Wideband Audio	Support for wideband (G.722 codec, adherence to TIA 920), including handset, headset, and speakerphone (see Q&A for details).
Codec Support	G.711a, G.711μ, G.729a, G.729ab, G.722, and iLBC audio compression codecs are supported (see Q&A for details).
Speakerphone	Full-duplex speakerphone with acoustic echo cancellation.
Messages Key	Provide direct access to voicemail.
Directories Key	Ready access to missed, received or placed calls (plus intercom history and directories). Incoming messages are identified and categorized on the display, allowing users to quickly and effectively return calls using direct dial-back capability. Corporate directory integrates with the Lightweight Directory Access Protocol Version 3 (LDAP3) standard directory.
Settings Key	Allows user to adjust display contrast, select background images (if available), and select ringer sounds through the User Preference menu. Network Configuration preferences also can be set up (usually by the system administrator). Configuration can be set up either automatically or manually for Dynamic Host Control Protocol (DHCP), Trivial File Transfer Protocol (TFTP), Cisco Unified Communications Manager, and backup Cisco Unified Communications Manager instances. Other available Settings submenus include Device Configuration, Security Configuration, and Model Information.

Services Key	Allows users to quickly access diverse information such as weather, stocks, quote of the day, or any Web-based information using XML.
Help Button	Online Help gives users information about the phone keys, buttons, and features.
Speakerphone, Mute, and Headset Buttons	Speakerphone includes Speaker On/Off, Microphone Mute, and Headset buttons that are lit when active. For added security, the audible dual tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.
Ethernet Switch	Internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100BASE-T Ethernet network through an RJ-45 interface with single LAN connectivity for both the phone and a colocated PC. System administrator can designate separate VLANs (802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.
Headset Port	Dedicated headset port eliminates the need for a separate headset amplifier and allows the handset to remain in its cradle, making headset use simpler. Both wideband (G.722) and narrowband headsets are supported.
Volume Control	Provides easy decibel-level adjustments for the speakerphone, handset, headset, and ringer. The handset is hearing aid-compatible. Additional volume control gain can be achieved using an inline headset amplifier.
Adjustable Foot-Stand	Stand is adjustable from flat to 60 degrees to provide optimum display viewing and comfortable use of all buttons and keys. The foot-stand is keyed to match standard wall-jack configurations for wall mounting. Optional wall-mount brackets are also offered.
Expansion Module Support	An optional add-on module, the Cisco Unified IP Phone Expansion Module 7914, provides 14 additional buttons for programming directory numbers or speed dials. Up to two expansion modules can be used.
Multiple Ring Tones	More than 24 defined user-selectable ring tones are available. Ring tones may also be personalized through use of the Cisco Unified Phone Application Suite.
Americans with Disabilities Act (ADA) Features	Handset is hearing aid-compatible and meets Federal Communications Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). Section 508 loudness requirements can be achieved using industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. Dial pad is also ADA-compliant.
Quality of Service (QoS) Options	Supports differentiated services code point (DSCP) and 802.1Q/p standards.
Security	Positive device identity through X.509v3 Certificates, digitally signed images, cryptographically secure provisioning, and secure signaling and secure media with AES-128. Cryptography is not enabled by default and may only be enabled through a cryptographically enabled CUCM. The phone also contains an 802.1X supplicant and supports EAPOL pass-through.
Language Support	Built-in support for more than 30 languages (dependent on Cisco Unified Communications Manager version).
Configuration Options	IP address assignment can be statically configured or configured through the DHCP client.

**Table 3 shows the temperature ratings.**

Temperature Variable	Description
Operating Temperature	32 to 104°F (0 to 40°C)
Relative Humidity	10 to 95% (noncondensing)
Storage Temperature	14 to 140°F (-10 to 60°C)

**Table 4 shows the ordering information-Phone/license**

Part Number	Description
CP-7962G	Cisco Unified IP Phone 7962G
<a href="#">CP-7962G=</a>	Cisco Unified IP Phone 7962G, spare
CP-7962G-CH1	Cisco Unified IP Phone 7962G, for Channels, with one station user license
CP-7962G-CCME	Cisco Unified IP Phone 7962G, for Channels, with one Cisco Unified Communications Manager Express station user license

Note: All Cisco Unified IP phones require the purchase of a phone technology license, regardless of call protocol being used.

**Table 5 shows the ordering information-Accessories**

Part Number	Description
CP-7914=	14-button expansion module. Up to two modules may be used.
CP-LCKNGWALLMOUNT=	Locking wall-mounting kit, flat (recommended version)
CP-WALLMOUNTKIT=	Nonlocking wall-mounting kit, slanted
CP-LCKNGWALLMNT2=	Locking wall-mounting kit, slanted
<a href="#">CP-PWR-CUBE-3=</a>	Local power adapter for sites where PoE is not available; refer to Table 6 to select the correct regional power cord. CP-PWR-CUBE-3= is compatible with and can replace CP-PWR-CUBE-2=.
<a href="#">CP-PWR-INJ=</a>	Single-port midspan power injector with integrated power supply, specifically designed and tested for use with all Cisco Unified IP Phones. May be used as an alternative to the existing Cisco phone local power adapter (CP-PWR-CUBE-3=), and can support a maximum distance of 100 meters between an unpowered switch and a Cisco Unified IP Phone.

**Table 6 shows the ordering information-AC Country Power Cords**

Part Number	Description
CP-PWR-CORD-AP=	Asia Pacific
CP-PWR-CORD-AR=	Argentina
CP-PWR-CORD-AU=	Australia
CP-PWR-CORD-CE=	European Community
CP-PWR-CORD-CN=	China
CP-PWR-CORD-JP=	Japan
CP-PWR-CORD-NA=	North America
CP-PWR-CORD-SW=	Switzerland
CP-PWR-CORD-UK=	United Kingdom

## Get More Information

Do you have any question about the CP-7962G?

Contact us now via [info@hi-network.com](mailto:info@hi-network.com).

## Specification

CP-7962G Specification	
Model info	CP-7962G

Product Type	IP phone
Codec Support	G.711a, G.711μ, G.729a, G.729ab, G.722, and iLBC audio compression codecs are supported
Speakerphone	Full-duplex speakerphone with acoustic echo cancellation.
Messages Key	Provide direct access to voicemail
Directories Key	Corporate directory integrates with the Lightweight Directory Access Protocol Version 3 (LDAP3) standard directory.
Settings Key	preferences also can be set up (usually by the system administrator). Configuration can be set up either automatically or manually for Dynamic Host Control Protocol (DHCP), Trivial File Transfer Protocol (TFTP), Cisco Unified Communications Manager, and backup Cisco Unified Communications Manager instances. Other available Settings submenus include Device Configuration, Security Configuration, and Model Information.
Help Button	Online Help gives users information about the phone keys, buttons and features
Expansion Module Support	An optional add-on module, the Cisco Unified IP Phone Expansion Module 7914, provides 14 additional buttons for programming directory numbers or speed dials. Up to two expansion modules can be used.
Mutiple Ring Tones	More than 24 defined user-selectable ring tones are available. Ring tones may also be personalized through use of the Cisco Unified Phone Application Suite.
Language Support	morethan 30 languages.
Dimensions (H x W x D)	8.2 x 10.5 x 6 in. (20.32 x 26.67 x 15.24 cm)
Weight	3.5 lb (1.6 KG)
Phone Software Requirements	Supported in 8.3(2) and greater
Call Control compatibility	Supported in Cisco Unified Communications Manager Versions 4.1(3)sr5b, 4.2(3)sr2b, 4.3(1), 5.1.1(b), 5.1(2), 6.0(1) and greater Supported in Cisco Unified Communications Express and SRST Version 4.1
Signaling protocols	Skinnny Client Control Protocol (SCCP) and Session Initiation Protocol (SIP) with Cisco call control
License	SW-CCME-UL-7962: Communications Manager Express License For One 7962G Phone

## Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)



## Contact HI-NETWORK.COM For Global Fast Shipping

---

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223