

Get a Quote

Overview

Cisco Unified IP Phone 7975G demonstrates the latest advances in VoIP telephony, including wideband audio support, backlit color touchscreen display, and an integrated Gigabit Ethernet port. It addresses the needs of the executive or major decision maker, administrative assistants, and those working with bandwidth-intensive applications on collocated PCs.

Quick Specification

Figure 1 shows the Cisco Unified IP Phone 7975G.



Figure 2 shows the Close-Up of Display and Lighted Line Keys



Table 1 shows the Quick Specification.

Model	CP-7975G
Dimensions (H x W x D)	8.2 x 10.5 x 6 in. (20.32 x 26.67 x 15.24 cm)
Phone-Casing Composition	Acrylonitrile butadiene styrene (ABS) plastic in textured dark gray color with silver bezel
Power	Supports IEEE 802.3af PoE (Class 3). 48VDC is required; it can be supplied locally at the desktop using an optional AC-to-DC power supply (part number CP-PWR-CUBE-3=) or power injector (CP-PWR-INJ=). Local power options require a corresponding AC country cord.

Phone Software Requirements	Supported in 8.3(2) and greater
Call Control compatibility	Supported in Cisco Unified Communications Manager Versions 4.1(3) sr5b, 4.2(3) sr2b, 4.3(1), 5.1.1(b), 5.1(2), 6.0(1) and greater Supported in Cisco Unified Communications Express and SRST Version 4.1
Signaling Protocols	Skinnny Client Control Protocol (SCCP) and Session Initiation Protocol (SIP) with Cisco call control

Product Details

Table 2 shows the features of this IP Phone.

Feature	Description/Benefit
Display	5.6-inch (14 cm) graphical TFT color touchscreen display, 16-bit color depth, 320 x 240 effective pixel resolution, with backlight. Allows for greater flexibility of features and applications, and significantly expands the information viewed when using features such as Services, Information, Messages, and Directory. Display also supports localization requiring double-byte Unicode encoding for fonts.
Wideband Audio	Support for wideband (G.722 codec, adherence to TIA 920), including handset, headset, and speakerphone.
Codec Support	G.711a, G.711 μ , G.729a, G.729ab, G.722, and iLBC audio compression codecs are supported.
Speakerphone	Full-duplex speakerphone with acoustic echo cancellation.
Messages Key	Provides direct access to voicemail.
Directories Key	Ready access to missed, received or placed calls (plus intercom history and directories). Incoming messages are identified and categorized on the display, allowing users to quickly and effectively return calls using direct dial-back capability. Corporate directory integrates with the Lightweight Directory Access Protocol Version 3 (LDAP3) standard directory.
Settings Key	Allows user to adjust display brightness, select background images (if available), and select ringer sounds through the User Preference menu. Network Configuration preferences also can be set up (usually by the system administrator). Configuration can be set up either automatically or manually for Dynamic Host Control Protocol (DHCP), Trivial File Transfer Protocol (TFTP), Cisco Unified Communications Manager, and backup Cisco Unified Communications Manager instances. Other available Settings submenus include Device Configuration, Security Configuration, and Model Information.
Services Key	Allows users to quickly access diverse information such as weather, stocks, quote of the day, or any Web-based information using XML.
Help Button	Online Help gives users information about the phone keys, buttons, and features.
Speakerphone, Mute, and Headset Buttons	Speakerphone includes Speaker On/Off, Microphone Mute, and Headset buttons that are lit when active. For added security, the audible dual tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.
Navigation Cluster with 'Select' Button	Four-way navigation cluster allows users to scroll vertically and horizontally. At the center of the cluster is a 'Select' button that can be used for selection of an in-focus item (for example, to open an underlying menu)
Display Button	Indicates when phone is in power-saving sleep/inactivity mode (button is lit), and can be used to awaken the display. Inactivity period is configured by the system administrator.
Ethernet Switch	Internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000 BASE-T Ethernet network through an RJ-45 interface with single LAN connectivity for both the phone and a collocated PC. System administrator can designate separate VLANs (802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.
Headset Port	Dedicated headset port eliminates the need for a separate headset amplifier and allows the handset to remain in its cradle, making headset use simpler. Both wideband (G.722) and narrowband headsets are supported.

Volume Control	Provides easy decibel-level adjustments for the speakerphone, handset, headset, and ringer. The handset is hearing aid-compatible. Additional volume control gain can be achieved using an inline handset amplifier.
Adjustable Foot-Stand	Stand is adjustable from flat to 60 degrees to provide optimum display viewing and comfortable use of all buttons and keys. The foot-stand is keyed to match standard wall-jack configurations for wall mounting. Optional wall-mount brackets are also offered.
Expansion Module Support	An optional add-on module, the Cisco Unified IP Phone Expansion Module 7914, provides 14 additional buttons for programming directory numbers or speed dials. Up to two expansion modules may be used.
Multiple Ring Tones	More than 24 defined user-selectable ring tones are available. Ring tones may also be personalized through use of the Cisco Unified Phone Application Suite.
Americans with Disabilities Act (ADA) Features	Handset is hearing aid-compatible and meets Federal Communications Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). Section 508 loudness requirements can be achieved using industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. Dial pad is also ADA-compliant.
Quality of Service (QoS) Options	Supports differentiated services code point (DSCP) and 802.1Q/p standards.
Security	Positive device identity through X.509v3 Certificates, digitally signed images, cryptographically secure provisioning, and secure signaling and secure media with AES-128. Cryptography is not enabled by default and may only be enabled through a cryptographically enabled CUCM. The phone also contains an 802.1X supplicant and supports EAPOL pass-through.
Language Support	Built-in support for more than 30 languages (dependent on Cisco Unified Communications Manager version).
Configuration Options	IP address assignment can be statically configured or configured through the DHCP client.

The Accessories

Table 3 shows the optional accessories of this IP phone.

Part Number	Description
CP-7914	14-button expansion module. Up to two modules may be used.
CP-LCKNGWALLMOUNT	Locking wall-mounting kit, flat (recommended version)
CP-WALLMOUNTKIT	Nonlocking wall-mounting kit, slanted
CP-LCKNGWALLMNT2	Locking wall-mounting kit, slanted
CP-PWR-CUBE-3	Local power adapter for sites where PoE is not available; refer to Table 6 to select the correct regional power cord. CP-PWR-CUBE-3 is compatible with and can replace CP-PWR-CUBE-2.
CP-PWR-INJ	Single-port midspan power injector with integrated power supply, specifically designed and tested for use with all Cisco Unified IP Phones. May be used as an alternative to the existing Cisco phone local power adapter (CP-PWR-CUBE-3), and can support a maximum distance of 100 meters between an unpowered switch and a Cisco Unified IP Phone.
CP-PWR-CORD-AP	Asia Pacific
CP-PWR-CORD-AR	Argentina
CP-PWR-CORD-AU	Australia
CP-PWR-CORD-CE	European Community
CP-PWR-CORD-CN	China
CP-PWR-CORD-JP	Japan
CP-PWR-CORD-NA	North America

CP-PWR-CORD-SW	Switzerland
CP-PWR-CORD-UK	United Kingdom

Get More Information

Do you have any question about the CP-7975G?

Contact us now via info@hi-network.com.

Specification

CP-7975G Specification	
General	
Product Type	VoIP phone
Body Color	Silver, dark gray
Body Material	ABS plastic
Phone Features	
Call Services	Voice Mail, Caller ID, Call Forwarding, Call Transfer, Call Hold
Dialer Type	Keypad
Dialer Location	Base
Conference Call Capability	Yes
Speakerphone	Yes (digital duplex)
Menu Operation	Yes
Function Buttons	Speakerphone button, directory button, navigator key, headset button, mute button
Volume Control	Yes
Ringer Control	Yes
Firmware Upgradable	Yes
Additional Functions	Web browser
Additional Features	On-hook dialing
IP Telephony	
Main Features	Multiple VoIP protocol support, integrated Ethernet switch
VoIP Protocols	SCCP, SIP
Voice Codecs	G.722, G.729a, G.729ab, G.711u, G.711a, iLBC
Quality of Service	IEEE 802.1Q (VLAN), IEEE 802.1p
IP Address Assignment	DHCP, static

Security	128-bit AES
Power Over Ethernet (PoE) Support	Yes
Network Protocols	TFTP
Network Ports Qty	2 x Ethernet 10Base-T/100Base-TX/1000Base-T
Voice Features	Echo cancellation (ECN)
Network Features	Class 3 PoE
Display	
Type	LCD display - color
Display Location	Base
Diagonal Size	5.6
Display Resolution	320 x 240 pixels
Color Depth	16-bit (65000 colors)
Display Information	Date, time
Backlit	Yes
Features	Wallpaper
Miscellaneous	
Connections	Headset jack
Hearing Aid Compatible	Yes
Placing / Mounting	Wall-mountable, table-top
Dimensions & Weight (Base)	
Width	10.5 in
Depth	6 in
Height	8 in
Weight	3.5 lbs

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales](#) or [Support](#)



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223