

Get a Quote

Overview

Serial and asynchronous high-speed WAN interface cards (HWICs) provide highly flexible connections for Cisco 1800, 1900, 2800, 2900, 3800, and 3900 Series Integrated Services Routers. These HWICs help customers enable applications such as WAN access, legacy protocol transport, console server, and dial access server. You can mix and match HWICs to tailor cost-effective solutions for common networking problems such as remote network management, external dial-modem access, low-density WAN aggregation, legacy protocol transport, and high-port-density support.

Cisco offers four new serial and asynchronous HWICs:

- Cisco 1-Port T1/Fractional T1 DSU/CSU WAN Interface Card (HWIC-1DSU-T1)
- Cisco 1-Port Serial WAN Interface Card (HWIC-1T)
- Cisco 2-Port Serial WAN Interface Card (HWIC-2T)
- Cisco 2-Port Asynchronous/Synchronous Serial WAN Interface Card (HWIC-2A/S)

Quick Specification

Model	HWIC-1T
Synchronous Support	Yes
Synchronous Maximum Speed (Per Port)	8 Mbps
Asynchronous Support	Yes
Asynchronous Maximum Speed (Per Port)	115.2 kbps
Bisync Support	Yes
Serial Protocols	EIA-232, EIA-449, EIA-530, EIA-530A, V.35, and X.21
Network Clock Synchronization	Yes
NEBS	Type 2/4

Product Details:

The Front Panel:



Get more information:

Do you have any question about the HWIC-1T?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Manufacturer	Cisco
Part Number	HWIC-1T
Device Type	Expansion module
Form factor	Plug-in module
Specifications	
Synchronous Support	Yes
Synchronous Maximum Speed (Per Port)	8 Mbps
Asynchronous Support	Yes
Asynchronous Maximum Speed (Per Port)	115.2 kbps
Bisync Support	Yes
Serial Protocols	EIA-232, EIA-449, EIA-530, EIA-530A, V.35, and X.21
Network Clock Synchronization	Yes
NEBS	Type 2/4
TelecommPTT	TBR1 and 2

	JATE Digital NEBS
Safety Approvals	UL 60950, CAN/CSA 22.2, CSA60950, GB 4943, AS/NZS 60950, EN60950, IEC 60950
Immunity	EN300386, CISPR24, EN55024, EN50082-1, 61000-4-2/3/4/5/6/8/11
Emissions	FCC Part 15 Class A, ICES-003 Class A, EN55022 Class A, CISPR22 Class A, AS/NZSCISPR22 Class A, VCCI Class A, EN 300386, EN61000-3-2/3, CNS13438
Physical Specifications	Singlewide HWIC, no slot restrictions Dimensions (H x W x D) 0.8 x 3.1 x 5.6 in. (2.1 x 7.9 x 14.2 cm)
Environmental Specifications	Operating temperature: 32 to 104°F (0 to 40°C) NEBS short-term operating temperature: 32 to 131°F (0 to 50°C) Storage temperature: -4 to 149°F (-20 to 65°C) Relative humidity: 10 to 90%, noncondensing
TelecommPTT	<ul style="list-style-type: none"> • TBR1 and 2 • JATE Digital • NEBS
Safety Approvals	<ul style="list-style-type: none"> • UL 60950 (United States) • CAN/CSA 22.2, CSA60950 (Canada) • GB 4943 (China) • AS/NZS 60950 (Australia/New Zealand) • EN60950 (Europe) • IEC 60950 (International)
Immunity	<ul style="list-style-type: none"> • EN300386 • CISPR24 • EN55024 • EN50082-1 • 61000-4-2/3/4/5/6/8/11
Emissions	<ul style="list-style-type: none"> • FCC Part 15 Class A • ICES-003 Class A • EN55022 Class A • CISPR22 Class A • AS/NZSCISPR22 Class A • VCCI Class A • EN 300386 • EN61000-3-2/3 • CNS13438
Physical Specifications	<ul style="list-style-type: none"> • Singlewide HWIC, no slot restrictions • Dimensions (H x W x D) 0.8 x 3.1 x 5.6 in. (2.1 x 7.9 x 14.2 cm)

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223