

Get a Quote

Overview

Cisco Catalyst WS-X4724-SFP-E line-card is designed for requiring line-rate capability for enterprise, mid-market and commercial core and distribution deployments. Integrated 24 SFP nonblocking ports with IEEE802.1AE Fiber Encryption and Cisco TrustSec capability in hardware, WS-X4724-SFP-E line-card delivers high-performance and secures user experience. This WS-X4724-SFP-E is similar with the WS-X4724-SFP-E=. The WS-X4724-SFP-E= is a spare one.

Quick Specification

Product Code	WS-X4724-SFP-E
Line-Card Type	Cisco Catalyst 4500 47xx E-Series Line Cards
Chassis Support	Supported on all 3, 6, 7 (R-E & R+E) and 10 (R-E & R+E) slot chassis
Supervisor Support	Supervisor Engine 8-E, Supervisor Engine 7-E, Supervisor Engine 7L-E
per-slot capacity	24 gigabits
Max Rated Power (W)	40
Rated MTBF (Hours)	1,139,510
Cisco IOS Software	Cisco IOS Software Release IOS-XE3.5.0E/15.2(1)E or later
L2-4 Jumbo Frame support	up to 9216 bytes

*All power numbers shown in Table 1 are maximum values recommended for facility power and cooling capacity planning. These figures are not indicative of the actual power draw during operation. Typical power draw is about 20 percent lower than the maximum value shown.

Get a Quote

Product Details:

The Front Panel:



Get more information:

Do you have any question about WS-X4724-SFP-E?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Model Name	WS-X4724-SFP-E
Type	E-Series Gigabit Ethernet SFP Line Cards
Number of Ports	24
Port Speed	1GbE/100Mbps
Port Type	Pluggables
Wire Rate	1:1
Standards	<ul style="list-style-type: none"> Gigabit Ethernet: IEEE 802.3z, IEEE 802.3x, IEEE 802.3ab, IEEE 803.3at, IEEE 802.3af, IEEE 802.3az 1000BASE-X (GBIC), 1000BASE-SX, 1000BASE-LX/LH, 1000BASE-ZX, CWDM
EtherChannel Technology	<ul style="list-style-type: none"> Gigabit EtherChannel: All 1000 Mbps ports 10 Gigabit EtherChannel: All 10Gbps ports IEEE 802.3ad (Link Aggregation Control Protocol): All 1000 Mbps ports Port Aggregation Protocol (PagP): Yes Number of ports per tuple: 8 EtherChannel and IEEE 802.3ad technology across line cards: Yes
Physical Dimensions	<ul style="list-style-type: none"> Occupies one slot in the Cisco Catalyst 4500 Series platform



Get a Quote

	<ul style="list-style-type: none"> • Dimensions (H x W x D): 1.2 x 14.25 x 10.75 in. (3.0 x 36.2 x 27.3 cm)
Environmental Conditions	<ul style="list-style-type: none"> • Operating temperature: 32° to 104°F (0° to 40°C) • Storage temperature: -40° to 167°F (-40° to 75°C) • Relative humidity: 10 to 90%, noncondensing • Operating altitude: -60 to 3000m
Safety Conditions	Fiber optic lasers: Class 1 laser products
Safety Certifications	<ul style="list-style-type: none"> • UL 1950 • EN 60950 • CSA-C22.2 no 950 • IEC 950 • IEC 60950-1, 2nd Ed. EN 60950-1, 2nd Ed. UL 60950-1, 2nd Ed. CAN/CSA-C22.2 No. 60950-1 2nd Ed.11
Electromagnetic Emissions Certifications	<ul style="list-style-type: none"> • FCC 15J Class A • VCCI Class A • CE Marking • EN 55022 Class A • EN 55024 Class A • CISPR 22 Class A • AS/NZ 3548 • NEBS Level 3 (GR-1089-CORE, GR-63-CORE) • ETSI ETS-300386-2 • EN 50121-4
ROHS Compliance	ROHS5
Max Rated Power (W)	40
Rated MTBF (Hours)	1,139,510



Get a Quote

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223