

Overview

The Huawei EchoLife HG8240H is a bridging-type ONT used in the Huawei all-optical access solution. It implements ultra-broadband access through the GPON technology.

It provides 4 GE ports and 2 POTS ports. The high-performance forwarding capability ensures the service experience of voice, data and HD video services, and provides users with ideal terminal solutions and future-oriented service support capabilities.

Quick Specification

Table 1 shows the Quick Specification.

Model	EchoLife HG8240H
Dimensions (W x D x H)	176 mm x 138.5 mm x 28 mm
Weight	< 500 g
Operating Temperature	0°C to +40°C
Operating Humidity	5%RH to 95%RH (non-condensing)
Power Adapter Input	100–240 V AC, 50–60 Hz
System Power Supply	11–14 V DC, 1 A
Static Power Consumption	4 W
Maximum Power Consumption	10 W
Ports	4GE + 2POTS
Indicators	POWER/PON/LOS/LAN/TEL

Figure 1 shows the appearance of EchoLife HG8240H.





Product Details

Port Parameters

GPON Port	<ul style="list-style-type: none"> • Class B+ • Receiver sensitivity: -27dBm • Wavelengths: US 1310nm, DS 1490nm • Wavelength blocking filter (WBF) • Flexible mapping between GEM Port and TCONT • GPON: consistent with the SN or password authentication defined in G.984.3 • Bi-directional FEC • SR-DBA and NSR-DBA
Ethernet Port	<ul style="list-style-type: none"> • Ethernet port-based VLAN tags and tag removal • 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission • QinQ VLAN • Limit on the number of learned MAC addresses • MAC address learning • Local switching/isolation based on Ethernet ports • Transparent transmission of IPv6 packets at Layer 2
POTS Port	<ul style="list-style-type: none"> • Maximum REN: 4 • G.711A/μ, G.729a/b, and G.722 encoding/decoding • T.30/T.38/G.711 fax mode • DTMF • Emergency calls (with the SIP protocol)

Function List

Smart Service	<ul style="list-style-type: none"> • Association of one account with two POTS ports • L2 forwarding: 1G uplink, 2G downlink
Smart Interconnection	<ul style="list-style-type: none"> • SIP/H.248 auto-negotiation
QoS	<ul style="list-style-type: none"> • Ethernet port rate limitation • 802.1p priority • SP/WRR/SP+WRR • Broadcast packet rate limitation • Flow mapping based on the VLAN ID, port ID, or/and 802.1p
Security	<ul style="list-style-type: none"> • MAC address filtering
Power Saving	<ul style="list-style-type: none"> • Indicator power saving • Power consumption reduction of idle components in power-saving state • COCv4
Smart O&M	<ul style="list-style-type: none"> • Variable-length OMCI messages





	<ul style="list-style-type: none"> • Active/Passive rogue ONT detection and isolation • PPPoE/DHCP simulation testing • Call emulation, and circuit test and loop-line test
Multicast	<ul style="list-style-type: none"> • IGMP v2/v3 snooping • MLD v1/v2 snooping • Fast leave • VLAN tag translation, transparent transmission, and removal for downstream multicast packets • IGMP/MLD protocol packet rate limitation
Common O&M	<ul style="list-style-type: none"> • OMCI/Web UI • Dual-system software backup and rollback • 802.1ag Ethernet OAM • Optical link measurement and diagnosis • Loopback check

Get More Information

Do you have any question about the EchoLife HG8240H?

Contact us now via info@hi-network.com.

Specification

EchoLife HG8240H Specification	
Dimensions (W x D x H)	176 mm x 138.5 mm x 28 mm
Weight	< 500 g
Operating Temperature	0°C to +40°C
Operating Humidity	5%RH to 95%RH (non-condensing)
Power Adapter Input	100–240 V AC, 50–60 Hz
System Power Supply	11-14 V DC, 1 A
Static Power Consumption	4 W
Maximum Power Consumption	10 W
Ports	4GE + 2POTS
Indicators	POWER/PON/LOS/LAN/TEL
GPON Port	<ul style="list-style-type: none"> • Class B+ • Receiver sensitivity: -27dBm • Wavelengths: US 1310nm, DS 1490nm • Wavelength blocking filter (WBF) • Flexible mapping between GEM Port and TCONT • GPON: consistent with the SN or password authentication defined in G.984.3





Get a Quote

	<ul style="list-style-type: none">• Bi-directional FEC• SR-DBA and NSR-DBA
Ethernet Port	<ul style="list-style-type: none">• Ethernet port-based VLAN tags and tag removal• 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission• QinQ VLAN• Limit on the number of learned MAC addresses• MAC address learning• Local switching/isolation based on Ethernet ports• Transparent transmission of IPv6 packets at Layer 2
POTS Port	<ul style="list-style-type: none">• Maximum REN: 4• G.711A/μ, G.729a/b, and G.722 encoding/decoding• T.30/T.38/G.711 fax mode• DTMF• Emergency calls (with the SIP protocol)

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

