

[Get a Quote](#)

Overview

Huawei S5700-48TP-PWR-SI supports 44 PoE+ 10/100/1000BASE-T ports and 4 combo ports (10/100/1000BASE-T (PoE+) + 100/1000BASE-X). It has no Power supply, needs to purchase additional power W0PSA5000.

Quick Specification

Table 1 shows the quick specification.


Model	S5700-48TP-PWR-SI
Part Number	02352371
Downlink Ports	44 PoE+ 10/100/1000BASE-T ports
Uplink Ports	4 combo ports (10/100/1000BASE-T (PoE+) + 100/1000BASE-X)
Forwarding Performance	256 Gbit/s
Switching Capacity	72 Mpps
Stack	Supported
Stack Ports	Two stack ports available on each stack card
Power	Two power module slots (No Power supply, need to purchase additional power)
Heat Dissipation	Pluggable fan modules for forced air cooling
Memory (RAM)	256 MB
Flash	32 MB
Dimensions (W x D x H)	44.2 cm x 42 cm x 4.36 cm
Package Weight	11.89 Kg

Figure 1 shows the appearance of S5700-48TP-PWR-SI.



Product Details

Figure 2 shows the front panel of S5700-48TP-PWR-SI.



Note:

(1)	Forty-four PoE+ 10/100/1000BASE-T ports	(4)	ETH management port
(2)	Four combo ports (10/100/1000BASE-T (PoE+) + 100/1000BASE-X)	(5)	USB port
(3)	One console port		

· There are one rear card slot, one fan slot and two power module slots on the back panel.

The Transceiver

Table 2 shows the recommended transceivers.

Model	Description
GE-SFP Optical Transceiver	
SFP-1000BaseT	Electrical Transceiver, SFP, GE, Electrical Interface Module (100m, RJ45)
eSFP-GE-SX-MM850	Optical Transceiver, eSFP, GE, Multi-mode Module (850nm, 0.55km, LC)
SFP-GE-LX-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module (1310nm, 10km, LC)
S-SFP-GE-LH40-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module (1310nm, 40km, LC)
S-SFP-GE-LH40-SM1550	Optical Transceiver, eSFP, GE, Single-mode Module (1550nm, 40km, LC)
10G-SFP+ Optical Transceiver	
SFP-10G-USR	10GBase-USR Optical Transceiver, SFP+, 10G, Multi-mode Module (850nm, 0.1km, LC)
OMXD30000	Optical Transceiver, SFP+, 10G, Multi-mode Module (850nm, 0.3km, LC)
OSX010000	Optical Transceiver, SFP+, 10G, Single-mode Module (1310nm, 10km, LC)

Compare to Similar Items

Table 3 shows the comparison of Huawei S5700-48TP-PWR-SI and S5700-52C-PWR-EI.

Models	S5700-48TP-PWR-SI	S5700-52C-PWR-EI
Downlink Ports	44 × PoE+ 10/100/1000BASE-T ports	48 × PoE+ 10/100/1000BASE-T ports
Uplink Ports	Four combo ports (10/100/1000BASE-T (PoE+) + 100/1000BASE-X)	Sub-cards supported the uplink ports.
Power Supply	No Power supply, need to purchase additional power	No Power supply, need to purchase additional power
PoE Supported	Yes	Yes
Software Version	Standard	Enhanced

Get More Information

Do you have any question about the S5700-48TP-PWR-SI (02352371)?

Contact us now via info@hi-network.com.

Specification

S5700-48TP-PWR-SI Specification	
Manufacturer	Huawei
Manufacturer Part Number	S5700-48TP-PWR-SI
Form Factor	Fixed, Stackable
Switch Port	44 GE PoE ports, 4 GE Combo ports
Power Over Ethernet (PoE)	POE Switch, support POE+
Extended slot	One extended slot for a stack card
Max Stack bandwidth	48Gbps
DRAM Memory	256 MB
Flash Memory	32 MB
Performance	
Forwarding performance	72 Mpps
MAC address table	IEEE 802.1d compliance
	32 K MAC address entries
	MAC address learning and aging

	Static, dynamic, and blackhole MAC address entries
	Packet filtering based on source MAC addresses
VLAN	4 K VLANs
Reliability	RRPP ring topology and RRPP multi-instance
	Smart Link tree topology and Smart Link multi-instance, providing the millisecond-level protection switchover
	SEP
	STP, RSTP, and MSTP
	BPDU protection, root protection, and loop protection
	E-Trunk
IP routing	Static routing, ECMP
	RIPv1, RIPv2 and RIPv2
IPv6 features	Neighbor Discovery (ND)
	Path MTU (PMTU)
	IPv6 ping, IPv6 tracer, and IPv6 Telnet
	ACLs based on the source IPv6 address, destination IPv6 address, Layer 4 ports, or protocol type
	MLD v1/v2 snooping
	6to4 tunnel, ISATAP tunnel, and manually configured tunnel
Multicast	IGMP v1/v2/v3 snooping and IGMP fast leave
	Multicast forwarding in a VLAN and multicast replication between VLANs
	Multicast load balancing among member ports of a trunk
	Controllable multicast
	Port-based multicast traffic statistics
QoS/ACL	Rate limiting on packets sent and received by an interface
	Packet redirection
	Port-based traffic policing and two-rate three-color CAR
	Eight queues on each port
	WRR, DRR, SP, WRR+SP, and DRR+SP queue scheduling algorithms
	Re-marking of the 802.1p priority and DSCP priority
	Packet filtering at Layers 2 through 4, filtering out invalid frames based on the source MAC address, destination MAC address, source IP address, destination IP address, port number, protocol type, and VLAN ID
	Rate limiting in each queue and traffic shaping on ports
Security	User privilege management and password protection
	DoS attack defense, ARP attack defense, and ICMP attack defense
	Binding of the IP address, MAC address, interface, and VLAN
	Port isolation, port security, and sticky MAC

	Blackhole MAC address entries
	Limit on the number of learned MAC addresses
	802.1x authentication and limit on the number of users on an interface
	AAA authentication, RADIUS authentication, HWTACACS authentication, and NAC
	SSH v2.0
	Hypertext Transfer Protocol Secure (HTTPS)
	CPU defense
	Blacklist and whitelist
Management	
Management and maintenance	Stacking
	MAC Forced Forwarding (MFF)
	Virtual cable test
	Port mirroring and RSPAN (remote port mirroring)
	Remote configuration and maintenance by using Telnet
	SNMP v1/v2/v3
	RMON
	Web NMS
	HGMP
	System logs and alarms of different levels
	GVRP
	MUX VLAN
Power Supply Specifications	
Power Device	Power supply - support PoE+
Power Redundancy	No
Voltage Required	AC 120/230 V (50/60 Hz)
Dimensions / Weight / Miscellaneous	
Width	44.2cm
Depth	43.6cm
Height	22.0cm
Weight	5.0kg
System Software	
Software Version	Standard Version
Manufacturer Warranty	
Service & Support	1 year warranty

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223