

## Datasheet

[Get a Quote](#)

### Overview

S5731-L4T2ST-RUA (4\*10/100/1000BASE-T ports, 1\*GE SFP port, 1\*10/100/1000BASE-T port, AC power, power adapter)

### Quick Specification

Model	S5731-L4T2ST-RUA
Part Number	98011770
Memory (RAM)	-
Flash memory	-
PoE	Not supported
Wide [mm]	185.0 mm
Depth [mm]	115.0 mm
Height [mm]	27.0 mm
Weight without packaging [kg(lb)]	0.74 kg (1.63 lb)
Weight with packaging [kg(lb)]	1.02 kg (2.25 lb)

## Datasheet

### Product Details:

#### The front panel:



#### The back panel:



Get more information:

Do you have any question about the S5731-L4T2ST-RUA 98011770?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

### Specific Data Sheet:

Part Number	98011770
Model	S5731-L4T2ST-RUA
Wide [mm]	185.0 mm
Depth [mm]	115.0 mm
Height [mm]	27.0 mm
Chassis height [U]	0.61
Weight with packaging [kg(lb)]	1.02 (2.25)
Weight without packaging [kg(lb)]	0.74 (1.63)
Typical power consumption [W]	4.88 W (device) 5.08 W (device + power adapter)

# Datasheet

Maximum power consumption [W]	5.06 W (device) 5.26 W (device + power adapter)
Typical heat dissipation [BTU/hour]	16.65 (device) 17.33 (device + power adapter)
Maximum heat dissipation [BTU/hour]	17.27 (device) 17.95 (device + power adapter)
Heat dissipation mode	Natural heat dissipation
Power supply mode	Power adapter
Rated input voltage [V]	Power adapter input: 100–240 V AC; 50/60 Hz Power adapter output: 12 V DC
Input voltage range [V]	Power adapter input: 90–290 V AC; 47–63 Hz
Maximum input current [A]	1 A
Number of card slots	0
Number of power slots	0
Memory	--
Flash memory	--
Redundant power supply	Not supported
Types of fans	None
Noise at normal temperature (acoustic pressure) [dB(A)]	Noise-free (no fans): < 20
Noise at normal temperature (acoustic power) [dB(A)]	Noise-free (no fans): < 30
Airflow direction	-
Long-term operating temperature [°C(°F)]	-5°C to +45°C (23°F to 113°F) at an altitude of 0-1800 m (0-5906 ft.)
Short-term operating temperature [°C(°F)]	Not supported
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Restriction on the operating temperature variation rate	When the altitude is 1800-5000 m (5905.44-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (721.78 ft.). The device cannot start when the temperature is lower than 0°C (32°F). The operating temperature of a device ranges from -5°C to +45°C (23°F to 113°F) when the device uses the following optical modules: - GE optical modules with a transmission distance of less than or equal to 10 km
Long-term operating relative humidity [RH]	5% RH to 95% RH (non-condensing)
Long-term operating altitude [m(ft.)]	0–5000 m (0–16404 ft.)
Storage altitude [m(ft.)]	0-5000 m (0-16404 ft.)
MTBF [year]	83.23
MTTR [hour]	2
Availability	>0.99999
Maximum number of physical ports on the entire device	6

## Datasheet

Maximum number of 100GE ports	0
Maximum number of 40GE ports	0
Maximum number of 25GE ports	0
Maximum number of 10GE ports	0
Maximum number of GE ports	6
Maximum number of FE ports	5
1000M electrical interface	4
1000M optical interface	1
USB	Not supported
Console port	Not supported
Eth Management port	Not supported
Service port surge protection	Common mode: $\pm 6$ kV
Power supply surge protection	Power adapter: $\pm 6$ kV in differential mode and $\pm 6$ kV in common mode
RPS input	Not supported
PoE	Not supported

## Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

 Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

 Email: [info@hi-network.com](mailto:info@hi-network.com)

 Skype: [echo.hinetwork](https://www.skype.com/add?contact=echo.hinetwork)

WhatsApp Business: +8618057156223